

# HMA 2 / HMA 2A Series

## Direct - Fired Gas Burners

### Two Stage Combustion Technology

★ **MADE** in the USA ★



HMA 2 / HMA 2A

*Higher Temperature Rise*  
*Wider Operation Range*  
*Shorter, More Stable Flame*  
*and Lower Overall Emissions*

#### *Midco's Own Two Stage Technology in Direct-Fired Gas Burners*

Midco International's innovative two stage combustion burner is not just a modification or improvement of the old, but a completely different approach to direct-fired combustion. The two-stage combustion improves control of the flame process, meets and exceeds the ANSI Standards while outperforming the competition. By having two separate flames within the burner combustion zone, the flame is more stable, shorter and cleaner, permitting the reduction of emissions levels and allowing for higher temperature rise and higher tolerance to varying conditions when placed in the profile opening.

#### *Two Stage Combustion*

*Provides Unsurpassed  
Flame Stability and  
Lower Emissions*

#### *Burner Sections Available in*

- *Cast Iron*
- *Aluminum or*
- *Nickel Plated*



Midco<sup>®</sup>  
INTERNATIONAL

Midco<sup>®</sup> International Inc.  
4140 West Victoria Street  
Chicago, Illinois 60646  
toll free 866.705.0514  
tel 773.604.8700  
fax 773.604.4070  
web [www.midcointernational.com](http://www.midcointernational.com)  
e-mail [sales@midcointernational.com](mailto:sales@midcointernational.com)







# Specifications

* Firing rate	Gas Manifold Pressure	Pressure Drop Across Burner	Pilot Capacity	Pilot Manifold Pressure	Burner Turn-down Ratio	Flame Length	Air Velocities Across Burner
Up to 750,000 Btu/hr/ft	NG 4.2 - 8" W.C. LP 1.6 - 3" W.C.	0.05 to 1.4" W.C.	12,000 Btu/hr	NG 3.5" W.C. LP 2.0" W.C.	30 to 1	10" full ** firing rate	800 fpm to 4,000 fmp ***

\* Firing rate is dependent on the pressure drop across the burner.  
 \*\* Flame length depends on design pressure drop and is measured from the end of the baffle.  
 \*\*\* For other operating velocities contact our Engineering Department.

## Two Staged Technology for Direct-Fired Applications Plus Flexibility in Configuration

Straight, elbow and tee sections easily configure to desired capacity maximizing efficiency for installation and performance. Burners may be ignited by proven pilot or direct spark. Pilots are available for flame rectification or ultraviolet detection. Contact the Midco OEM sales team for specifications.



## Features and Benefits



**Reduced NO<sub>2</sub> and CO Emissions:** Lower emissions levels that are required to pass the ANSI Z83.4 and Z83.18 standards.



**Higher Temperature Rise:** The two stage combustion process lowers NO<sub>2</sub> emissions which is the limiting factor in temperature rise.



**Increased Capacity:** Up to 750,000 BTU's per foot. (Higher BTU levels can be achieved if ANSI Z83 Standards for CO and NO<sub>2</sub> emissions are not of a concern. Process heaters can fire up to 1,000,000 BTU's a foot or more.)



**Increased Differential Pressure Drop and Higher Velocities:** HMA-2 / HMA-2A burners can operate between 0.05" to 1.4" W.C. differential pressure range or in air velocity between 800 fpm to 4000 fpm.



**Flame Stability:** Two stage combustion provides better flame stability and emission control, allowing for a shorter flame and easier profile configuration.



**Reduced Shipping Costs:** A smaller, lighter casting than the competition's, can cut your freight costs up to 50%.



**Turndown:** 30-1 turndown can easily be achieved with proper modulation control and valves. (Higher turndown possible depending on equipment design.)



**Casting Choices:** Burner sections are available in iron, aluminum and nickel plated castings.

*Do you need assistance in burner selection or installation? Just call our OEM Sales Team at Midco International direct today (toll free 866 705 0514) or visit our web site at [www.midcointernational.com](http://www.midcointernational.com) to find out more about our HMA line of burners.*



★ MADE in the USA ★

We proudly design, manufacture and assemble our products in Chicago, Illinois, USA.

Midco® International Inc. - 4140 West Victoria Street - Chicago, Illinois 60646 - toll free: 866 705 0515  
 tel: 773.604.8700 - fax: 773.604.4070 - web: [www.midcointernational.com](http://www.midcointernational.com) - e-mail: [sales@midcointernational.com](mailto:sales@midcointernational.com)



721  
8474 83  
Printed in USA